

Shuttle XPC SB61G2V3

for Intel Pentium 4 / Celeron CPUs

DIMENSION (MM) L/W/H		300 x 200 x 185
WEIGHT (KG) N.W. / G.W.		2.85 / 4.48
CHASSIS MATERIAL / FRONT PANEL		Aluminum / Aluminum
MAINBOARD		FB61
CPU SUPPORT SOCKET TYPE (FSB)		Socket 478 (800 MHz)
CHIPSET	NORTHBRIDGE	Intel 865G
	SOUTHBRIDGE	ICH5
IDE INTERFACE		ATA 100 + Serial ATA150
EXPANSION SLOT		1x PCI, 1x AGP (8X)
MEMORY (2 SLOTS / TOTAL MAX. 2 GB)		DDR 400
GRAPHICS	CHIPSET	Intel Extreme Graphics 2
	SHARED MEMORY	64 MB
AUDIO		6 Channel Audio
DRIVE BAYS		1x 5 1/4", 2x 3 1/2"
FRONT PANEL	USB 2.0	2
	FIREWIRE (IEEE 1394)	1 (4 Pin)
	LINE-IN / -OUT / MIC	Yes / Yes / Yes
	SPDIF	
REAR PANEL	USB 2.0	4
	FIREWIRE (IEEE 1394)	1 (6 Pin)
	LINE-IN / -OUT	Yes / Yes
	SPDIF	Optical IN + OUT
	SERIAL PORT	1
	PARALLEL PORT	Optional
	VGA	1
	TV-OUT	Optional
LAN	100 MBit (Realtek 8100B)	
WIRELESS LAN		Optional
MEMORY CARD READER		Optional
POWER SUPPLY		250 W SilentX (PFC)
HOT FEATURES	BURN PROOF	
	AGP PROOF	Yes
	HYPER-THREADING	Yes
	DUAL CHANNEL DDR	Yes
AVAILABLE COLOURS		Silver
OTHER		Serial ATA, Prescott is supported



Shuttle article number
SB61G2V3
Shuttle ordner number
PC-SB61G2V3



UPC code of this product

Package Content: XPC aluminum case with pre-mounted mainboard FB61, pre-mounted I.C.E. cooling solution, power supply, drivers CD, FDD-, HDD cables and power cord, mounting kit (screws, wire straps, adhesives, thermal grease), flexible front feet, printed mainboard manual and XPC installation guide

SHUTTLE WEBSITE: WWW.SHUTTLE.COM

Shuttle Computer Handels GmbH
Fritz-Strassmann-Str. 5
25337 Elmshorn / Germany

Tel. +49 (0) 4121 476 860
Fax. +49 (0) 4121 476 900
sales@spacewalker.de

Shuttle
Connecting Technologies